



SIGN	DATE	DESCRIPTION	APPROVER
△			
△			
△			

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

- Material:
- Insulator body: Thermoplastic (UL 94V-0)
 - Terminal body(house): Brass ,Ni plated
 - Contacts: Brass ,Tin plated
 - Terminal screw: Steel Zinc plating"-slot type

- Electrical cULus/FIMKO
- Voltage rating: 300VAC/300VAC
 - Current rating: 16A/17.5A
 - Wire range: 1.5mm²
Solid wire(AWG): 12-28
Stranded wire(AWG): 12-28
 - Torque: 3.5Lb-In./0.5Nm
 - Screw: M3
 - Wire strip length: 6-7mm
 - Withstanding Voltage: 1.6KV/2.5KV
 - Operating temperature: -40°C to +115°C
 - Soldering temperature: 250°C±10°C/5 Sec
 - Safety Approval:

RoHS Compliant

PART NUMBER:

OSTVIXX2153

No. of Poles	COLOR
02 2 Poles	0: Black
03 3 Poles	5: Green (Standard)
... ..	6: Blue
24 24 Poles	8: Grey

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ON-SHORE TECHNOLOGY, INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ON-SHORE TECHNOLOGY, INC.



TITLE OSTVI 5.08 SERIES 90° wire inlet Vertical-solid block(without cover)							
PART NO. OSTVIXX2153				DWG NO. OSTVIXX2153.DWG			
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance		
		Jacke	Jacke		UNIT: mm	X.	±0.50
		2008.11.13	2008.11.13		SCALE: NONE	X.X	±0.30
					SHEET: 01/01	X.XX	±0.10
					REV: B	X°	±1°