


Specifications:
 Current Rating: 3A AC,DC
 Voltage Rating: 250V AC,DC
 Contact Resistance: 20m ohm.Max
 Insulation Resistance: 1000M ohm.Min
 Withstanding Voltage: 1000V AC/Minute
 Operating Temperature Range:-25°C ~ +85°C

Material:
 Insulator: Thermoplastic(UL94V-0)
 Insulator Color: White
 Termini: Copper Alloy
 Plated: Tin Plated

Dimension Information:

Pin.No	Dim.A	Dim.B	Dim.C
02	2.00	6.00	4.85
03	4.00	8.00	6.85
04	6.00	10.00	8.85
05	8.00	12.00	10.85
06	10.00	14.00	12.85
07	12.00	16.00	14.85
08	14.00	18.00	16.85
09	16.00	20.00	18.85
10	18.00	22.00	20.85
11	20.00	24.00	22.85
12	22.00	26.00	24.85
13	24.00	28.00	26.85
14	26.00	30.00	28.85
15	28.00	32.00	30.85
16	30.00	34.00	32.85

How To Order
 CPCH31TRXX10
 └── No. Of Contacts



P.C.B Layout

RoHS Compliant

F				DRAWN: JAMIE	GENERAL TOLERANCE: .X=±0.25 .XX=±0.20	ON-SHORE TECHNOLOGY, INC.	DESCRIPTION: 2.00mm Wire to Board Connector	SIZE
E								
D				CHECKED: JERRY	UNIT: MM	PART NO: CPCH31TRXX10		
C					SCALE: 1:1			
B				APPROVAL: RORY	SHEET: 1/1			
A	21-OCT-2022		JAMIE		PROJECTION:			
REV	DATE	FILE	BY					