



ELECTRICAL CHARACTERISTICS

Contact Current Rating: 5A
 Dielectric Withstanding Voltage: AC 500V for 1 minute.
 Insulation Resistance: 1000Megohms Min. at 500VDC
 Operation Temperature : -55°C to +105°C

Material

Contact : Brass
 Contact plating: Gold flash over tin
 Insulator: PBT + 30%Glass Fiber (UL94V-0)
 Shell: Steel, Nickel plated

RoHS Compliant

Part Number

Pins
 D-XXS6-X

Leave blank for open holes (standard)
 C - clinch nuts (rear/bottom side) 5.8mm
 C3.8 - clinch nuts (rear/bottom side) 3.8mm
 T - threaded insert (front/top side) 5.8mm
 T3.8 - threaded insert (front/top side) 3.8mm

PIN	DIM	A	B	C	D	E
09		30.81	24.99	16.33	19.28	10.72
15		39.14	33.32	24.66	27.65	10.72
25		53.04	47.04	38.38	41.30	10.72
37		69.32	63.50	54.84	57.44	10.72

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ON-SHORE TECHNOLOGY, INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ON-SHORE TECHNOLOGY, INC.



TITLE		D Series - Solder Cup D-sub, socket			
PART NO.	D-XXS6-X	DWG NO.	D-XXS6.DWG		
APPROVED	CHECKED	DESIGNED	DRAWN	1200	
		Betty 2015.04.09	Karen 2015.04.09	Tolerance	
				UNIT: mm	.0 ±0.25 .0 ±2.0
				SCALE: NONE	.00 ±0.15 .00 ±1.0
				SHEET: 01/01	.000 ±0.05 .000 ±0.5
				REV.: B	