

SIGN	DATE	DESCRIPTION	APPROVER
△	07.26.2012	Added mounting hole diameter	

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

- NOTES:
- Rating: 300V 50A (UL)
 - Insulation Withstanding Voltage: AC2000V/MIN
 - Insulation Resistance: $\geq 500M\Omega$ or more at DC500V
 - Temperature Range: $-33^{\circ}C/+105^{\circ}C$
 - Screw Torque Value: 17.5lbf-in(UL)
 - Wire Range: 8-16AWG
 - Housing: Nylon PA66 UL94-V0
 - Screw M5, Steel, Zinc Plated
 - Wire protector: Stainless Steel
 - Terminal: Brass Nickle plated
 - Standard Color: Natural
 - Wire Protector Material: Stainless Steel without plating
 - Terminal: Brass with Ni plating


Agency Approvals:  

RoHS Compliant

DIM	P	2	3	4	5	6	7	8	9	10	11	12
L		25.7	40.2	54.7	69.2	83.7	98.2	112.7	127.2	141.7	156.2	170.7
TOL(±)		0.08	0.12	0.16	0.20	0.24	0.28	0.32	0.36	0.40	0.44	0.48

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ON-SHORE TECHNOLOGY, INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ON-SHORE TECHNOLOGY, INC.



TITLE		ES1450 Series - 14.5mm Euro Strip, wire guard, flat base											
PART NO.		ES1450/XXDSFB (XX - number of poles per row)					DWG NO.		ES1450/XXDSFB.DWG				
APPROVED		CHECKED	DESIGNED	DRAWN	5020			Tolerance					
KSZ 2012.06.01		KSZ 2012.06.01	KSZ 2012.06.01	KSZ 2012.06.01	 UNIT: mm SCALE: NONE SHEET: 01/01			.X ±0.25 .XX ±0.075 .XXX ±0.05					
		REV: A											