


Transfer or duplication of this document as well as the utilisation or communication of its content are not permitted unless express consent is granted. Violations give rise to claims for damages. All rights reserved in case of patent, utility model or design patent registrations.



- Technical data**
- Nominal voltage: 150V/8A
PITCH:3.5mm
 - Insulation Withstanding Voltage:
AC 1300V/MIN
 - Insulation Resistance:
1000MΩ or more at DC500V
 - Operating temperature range:-40°C - 115°C
 - Soldering temperature range: 250°C±10°C/5sec
 - Undimensioned Tolerances:

Dim.L=(P-1)x3.5+4.4		
Dim.B=(P-1)x3.5		
P=1/2 Number of poles (04-48P)		
0-30mm	Dim B	Dim L
over 30mm-60mm	±0.15	±0.20
over 60mm-90mm	±0.20	±0.25
over 90mm	±0.25	±0.30
		±0.40

- Safety approval:
- RoHS Compliance

Part No.: **OSTKEXX1350**

<p>No. of Poles</p> <p>02 2 Poles</p> <p>03 3 Poles</p> <p>... ..</p> <p>24 24 Poles</p>	<p>COLOR</p> <p>0: Black</p> <p>2: Red</p> <p>3: Orange</p> <p>4: Yellow</p> <p>5: Green (Standard)</p> <p>6: Blue</p> <p>8: Gray</p>
--	---

Nonstandard colors
Mins could apply

2	PIN	COPPER	TIN PLATED	P
1	BODY	PA66 UL94V-0	ALL COLOR	1
ITEM	NAME OF PART	MATERIAL	NOTES	Q'TY
DWG.	WF. Zhang	DATE	2015.12.30	UNITS: MM SHEET: 1 OF 1 Tolerance
CHK.	WF. Zhang	DATE	2016.09.26	SCALE: NONE 2.5:1 (:) REV.: A
APP.		DATE		TITLE: OSTKE 3.5 Series with engagement nose type 180D
				PART NO. OSTKEXX1350
				DWG NO. OSTKEXX1350.dwg

	SIGN	DESCRIPTION	CHK.	DATE
--	------	-------------	------	------

OST
ON-SHORE TECHNOLOGY, INC.