



PCB LAYOUT
(Top View)

| SIGN | DATE | DESCRIPTION | APPROVER |
|------|------|---|----------|
| | | <i>THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!</i> | |

Material:

- Housing: PBT Glass Filled (UL 94V-0)
- Color: Black
- Spring Wire: 0.45mm Diameter Phosphor Bronze
Gold Plating over Nickel
- Temp. Range: -40°C/+90°C
- Durability: 500 Mating cycles Min.

Electrical:

- Current rating: 1.5A Max.
- Voltage rating: 120V AC
- Insulation Resistance: 500 MΩ Min.
- Contact Resistance: 20mΩ Max.
- Dielectric Voltage: 1,000 Vrms for 60 sec. min.

● Part Number

PJ012-4P4CX-F

RoHS Compliant

| | | |
|--------------|--------|---------|
| Gold plating | 1=6u" | 2= 15u" |
| | 3=30u" | 4=50u" |



ON-SHORE TECHNOLOGY, INC.

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ON-SHORE TECHNOLOGY, INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ON-SHORE TECHNOLOGY, INC.

| | | | | | | | |
|---------------------|--|---|--------------------|----------------------|----------|------------------------------------|---|
| TITLE | | PJ012, 4 pos, 4 contact top entry, thru hole, with flange | | | | | |
| PART NO. | | PJ012-4P4CX-F | | DWG NO. | | PJ012-4P4CX-F.DWG | |
| APPROVED | | CHCKED | DESIGNED | DRAWN | CUST NO. | | Tolerance |
| Billy 2006.02.07 | | Johnn 2006.02.07 | Tony 2006.02.07 | Steven 2006.02.07 | | | X.XX ±0.25 X.XXX ±0.13 X.XXXX ±0.05 |
| | | | | SHEET: 01/01 | | UNIT: mm SCALE: NONE REV.: A | |